

ABSTRACT

5 ~~In a vessel (2) to which waste liquid which~~  
~~contains ink pigment, water and cleaning liquid~~  
~~used in a printer is supplied, a metal electrode~~  
~~plate (30a, 30b) which allows the waste liquid to~~  
~~flow therethrough is disposed to partition the~~  
~~inside of the vessel (2) into a first chamber (a)~~  
~~and a second chamber (b). A voltage is applied to~~  
~~the metal electrode plate (30a, 30b) while a~~  
10 ~~grounding electrode (20) is connected to the first~~  
~~chamber (a) to generate an electric field between~~  
~~the metal electrode plate (30a, 30b) and the~~  
~~grounding electrode (20) thereby to separate the~~  
~~waste liquid in the first chamber (a) into~~  
15 ~~regenerated cleaning liquid, regenerated water and~~  
~~the ink pigment.~~

In a vessel (2) to which waste liquid (11)  
which contains ink pigment, water and cleaning  
liquid used in a printer is supplied, a metal  
20 electrode plate (30a, 30b) which allows the waste  
liquid (11) to flow therethrough is disposed to  
partition the inside of the vessel (2) into a first  
region (a) and a second region (b). A high voltage  
from a high-voltage power supply (7) is applied to  
25 the metal electrode plate (30a, 30b) while a  
grounding electrode (20) is connected to the first  
chamber (a) to generate an electrostatic field

5

between the metal electrode plate (30a, 30b) and the grounding electrode (20) so that the water and the ink pigment are electrostatically agglomerated from the waste liquid (11) making use of electrophoresis of the ink pigment by the electrostatic field thereby to separate the waste liquid in the first region (a) into the cleaning liquid, water and ink pigment.